

SCOPE OF ACCREDITATION TO ISO/IEC 17025:2017

TRIALON CORPORATION

Michigan Testing and Validation Center- Auburn Hills 3000 University Drive Auburn Hills, MI 48326

Brad Soule Email: bsoule@trialon.com Phone 810-265-0105 Gregory Stetkiw Email: gstetkiw@trialon.com Phone: 810-341-7980 Shane Deford Email: sdeford@trialon.com Phone: 810-908-4107

Website: http://www.trialon.com

MECHANICAL

Valid To: September 30, 2024 Certificate Number: 1123.11

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory to perform the following tests using the parameters and methods listed below on the following products and materials: <u>abrasives</u>; <u>automotive components</u>; <u>coatings</u>; <u>glass and glass products</u>; <u>textiles</u>; <u>instrument clusters</u>; and circuit boards.

| Test Type | Test Parameters | Test Methods/Standard |
|---|-----------------|--|
| High/Low/Cyclic Temperature without Humidity ¹ | (-70 to 300) °C | Including but not limited to the following: EPS-24126248; EPS-24138553; FCA CS.00056 sections 5.3.1, 5.3.2, 5.3.3, 5.3.4; Ford CEPT:00:00-E-412 sections 5.1, 5.2, 5.3, 5.4, 5.5, 5.17; GMW 3172² sections 9.4.1- 9.4.3; GMW 3191 section 4.4; USCAR-2 section 5.6.3; MIL-STD-810(G,H) methods 501, 502; MIL-STD-202(G,H method 108; JDQ 53.3; ISO 16750-4; Hyundai/KIA ES95400-10; IEC 60068-2-14 |

| Temperature Capability with Humidity ¹ | (-50 to 150) °C (30% to 95%) RH | Including but not limited to the following: EPS-24126248; EPS-24138553; FCA CS.00056 sections 5.3.6, 5.3.7; Ford CEPT:00:00-E-412 sections 5.8, 5.20; GMW 3172² sections 9.4.5, 9.4.6; GMW 3191 sections 4.4.3, 4.4.4; USCAR-2 sections 5.6.2; USCAR-21 section 4.5.4; MIL-STD-810(G,H) method 507; MIL-STD-202(G,H) methods 103, 106; JDQ 53.3; Hyundai/KIA ES95400-10; ISO 16750-4; IEC 60068-2-38; IEC 60068-2-78 |
|--|------------------------------------|--|
| Thermal Shock ¹ | (-70 to 300) °C Air to Air | Including but not limited to the following: EPS-24126248; EPS-24138553; FCA CS.00056 section 5.3.5; Ford CEPT:00:00-E-412 sections 5.6, 5.7; GMW 3172² section 9.4.2; GMW 3191 section 4.4.2; USCAR-2 section 5.6.1; USCAR-21 section 4.5.5; MIL-STD-810(G,H) method 503; MIL-STD-202(G,H) method 107; JDQ 53.3; ISO 16750-4 |
| Force Testing Tension and Compression ¹ | Up to 10 kN | Including but not limited to the following: EPS-24126248; EPS-24138553; FCA CS.00056 section 5.4.2; Ford CEPT:00:00-E-412; GMW 3172 ² section 9.3.7; GMW 3191; USCAR-2; USCAR-21 |

| Microscopic Evaluation/Visual Examination/Microsection Analysis (Cross Sectioning) ¹ | (3x to 10,000x) | IPC-TM-650 (methods 2.1.1, 2.1.2, 2.1.5, and 2.1.10) |
|---|--|--|
| Dynamometer ¹ Driveline: Performance, Fatigue, Durability | Up to 75 HP, Torque Up to 4,166 ft/lbs, Speed Up to 10,000 RPM | GMW15788:2014 ² |
| Pressure ¹ | 0 to 2000 psi | ISO 20653 9K only |
| Liquid Flow ¹ | up to 39 gpm | ISO 20653 9K only |

| Test Type | Test Methods |
|---|---|
| | |
| Salt Fog/Mist | Including but not limited to the following: |
| | ASTM B117; |
| | FCA CS.00056 section 5.5.5; |
| | Ford CEPT:00:00-E-412 section 5.15; |
| | GMW 3172 ² section 9.4.7; |
| | GMW 3191 section 4.4.7; |
| | SAE J1455; NaCl only |
| | MIL-STD-202(G,H) method 101; |
| | MIL-STD-810(G,H) method 509; |
| | IEC 60068-2-11 |
| Real Time X-Ray | ASTM E94 |
| Optical Microscopy | Used in the test types Case Depth through SEM/EDS |
| Case Depth | ASTM B934 |
| Depth of Decarbonization | ASTM E1008 |
| Grain Size | ASTM E112 |
| Inclusion Content | ASTM E45 |
| Intergranular Corrosion | ASTM A262 |
| Macro – Etching | ASTM E340 |
| Plating Thickness | ASTM B659 |
| SEM/EDS | SEM/EDS Handbook |
| | |
| Rockwell Hardness Series 500 ¹ | ASTM E18; Rockwell HRBw, HRC, HR15Tw, HR30Tw; |
| LECO Hardness DM400-DTF | Leco, HK/300 |
| | |
| Gravel Impact ¹ | Including but not limited to the following: |
| Stavet Impact | EPS-24126248; |
| | SAE J400 |
| | SAL 1400 |
| | |
| Dust Exposure ¹ | Including but not limited to the following: |
| | EPS-24126248; |
| | EPS-24138553; |
| | DIN 40050-9e; |
| | FCA CS.00056 section 5.5.1; |
| | Ford CEPT:00:00-E-412 section 5.10.1; |
| | GMW 3172 ² section 9.5.1; |
| (A2I A C + NL 1122 11) D : 102 | |



| | IEC 60529; SAE J1455 2017, Alternate Method only ISO 20653 |
|----------------------------------|--|
| Chemical Resistance ¹ | Including but not limited to the following: EPS-24126248; EPS-24138553; GM3172 ² ; FCS CS CS.00056; Ford CETP 00.00-E-412; ISO 16750-5; GMW 14334; GMW 16449 |
| Water Spray | Including but not limited to the following: DIN 40050-9e; IP9K only FCA CS.00056 section 5.5.3; IP9K only GMW 3172 ² Section 9.5.2; IPK only USCAR-2 sections 5.6.74; IEC 60529; IP9 only ISO 20653 IP9K only |

I. Dimensional Testing

| Parameter | Range | Technique/Method |
|--------------------------|--------------------------------------|--|
| Linear (1D) ¹ | Up to 10 inches (+/0004in.) | Micrometers/ASME B18.3 and per Customer Requirements |
| | Up to 8 inches (+0001in.) | Optical Multi Sensor/Digital Microscope/ASME B18.3 and per Customer Requirements |
| | 40in. x 48in. x 24in. (+/0005in.) | Coordinate Measurement Machine (CMM) |
| Angle ¹ | Up to 360 degrees (+/- 0.5 degrees) | Optical Multi Sensor/Digital Microscope + CMM/ASME B18.3 and per Customer Requirements |
| Radius ¹ | 0.005 to 4.00 inches (+/- 0.001in.) | Optical Multi Sensor/Digital Microscope + CMM/ASME B18.3 and per Customer Requirements |

¹Also using customer specified methods directly related to the types of tests and parameters listed.



²This laboratory's scope contains withdrawn or superseded methods. As a clarifier, this indicates that the applicable method itself has been withdrawn or is now considered "historical" and not that the laboratory's accreditation for the method has been withdrawn including but not limited to GMW 3172 (2008, 2010, 2012, 2015,2018).

Page 5 of 5



Accredited Laboratory

A2LA has accredited

TRIALON CORPORATION

Auburn Hills, MI

for technical competence in the field of

Mechanical Testing

This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017 General requirements for the competence of testing and calibration laboratories. This laboratory also meets the requirements of any additional program requirements in the Mechanical field. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to joint ISO-ILAC-IAF Communiqué dated April 2017).



Presented this 6th day of September 2022.

Mr. Trace McInturff, Vice President, Accreditation Services

For the Accreditation Council

Certificate Number 1123.11

Valid to September 30, 2024

Revised March 30, 2023

For the tests to which this accreditation applies, please refer to the laboratory's Mechanical Scope of Accreditation.